



ExxonMobil Avgas

ExxonMobil Commercial Fuel , New Guinea

Product Description

ExxonMobil Aviation Gasoline is leaded fuel satisfying the requirements of ASTM D910, Standard Specification for Aviation Gasolines and DEF STAN 91-090 (DERD 2485). Critical properties must be controlled within defined limits for Aviation Gasoline to comply with ASTM D910 and DEF STAN 91-90 (DERD 2485) specifications.

ExxonMobil supplies one grade of Aviation Gasoline:

Aviation Gasoline 100LL (dyed blue) is a lower lead version of Aviation Gasoline 100 (0.56g lead /litre Max). It is excellent for use in piston engine powered private, commercial and military training aircraft. Aviation Gasoline 100LL has been approved by the major aircraft engine manufacturers for use in aircraft engines originally designed for operation on the following grades: 80/87, 100/130, and the discontinued 91/98. This grade is generally available in most regions worldwide.

Note that properties critical to aviation use (for example, vapour pressure and cleanliness) are not controlled to the same degree in automotive motor gasoline manufacture and handling. ExxonMobil Aviation does not support or approve the use of Automotive Gasoline as aircraft fuel.

Specifications

ExxonMobil Avgas 100LL meets the following industry specifications:	Avgas 100LL
ASTM D910	X
DEF STAN 91-090	X

Product Properties

	Avgas 100LL
Motor Method Octane	99.6 Min.
Supercharge Rating Performance No.	130.0 Min.
Tetraethyl Lead, mL/L	0.27 Min. / 0.53 Max.
Colour	Blue
10% Distillation, °C	75 Max.
40% Distillation, °C	75 Min.
50% Distillation, °C	105 Max.
90% Distillation, °C	135 Max.
Final Boiling Point, °C	170 Max.
Sum of 10% and 50%, °C	135 Min.
Recovery Volume, %	97 Min.
Residue Volume, %	1.5 Max.
Loss Volume, %	1.5 Max.

	Avgas 100LL
Vapour Pressure, kPa	38.0 Min. / 49.0 Max.
Freezing Point, °C	-58 Max.
Sulphur, Wt. %	0.05 Max.
Net Heat of Combustion, MJ/kg	43.50 Min.
Copper Strip Corrosion, 2 h @ 100 °C	No. 1 Max.
Oxidation Stability (5 h aging for ASTM D910, 16 h aging for DefStan 91-090)	
Potential gum, mg/100 mL	6 Max.
Lead Precipitate, mg/100 mL (ASTM D910 / DefStan 91-090)	3 Max. / 2 Max.
Water Reaction, Volume Change, mL	±2 Max.
Electrical Conductivity, pS/m *Limits apply when conductivity improver is used	50 Min. 600 Max.*

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

MAIN HAZARD: FIRE

Keep away from ignition sources.

Discharge your static electricity before fueling.

Fill portable containers on the ground.

Handle/Transport in closed or properly vented containers and systems, consistent with all applicable laws.

Harmful or fatal if swallowed.

Avoid breathing the vapors and skin contact.

Do not wash down spills with water. Prevent all spills from reaching water.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.


07-2022

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved