



## Mobilgard™ HSD CF4

ExxonMobil Marine , Vietnam

High Speed Diesel Engine Oil

### Product Description

Mobilgard™ HSD CF-4 variants, 15W-40 and 20W-50 are diesel engines oils that provide proven protection of diesel engines operating in marine service applications. Mobilgard HSD CF-4 engine oils are recommended by ExxonMobil for use in a wide range of diesel engines for use in a variety of operating environments in marine industries.

### Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up
TBN reserve	Deposit control
Component compatibility	Long seal and gasket life

### Applications

Mobilgard HSD CF-4 oils, 15W-40 and 20W-50 are designed to provide proven engine protection for marine diesel engines, including those models typically used in industries such as inland, coastal, fishing, dredging, offshore service and other similar applications.

### Specifications and Approvals

This product is recommended for use in applications requiring:	MOBILGARD HSD 15W-40 CF-4	MOBILGARD HSD 20W-50 CF-4
API CF-4	X	X

### Properties and Specifications

Property	MOBILGARD HSD 15W-40 CF-4	MOBILGARD HSD 20W-50 CF-4
Grade	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	1	1
Density @ 15 C, g/ml, ASTM D1298	0.87	0.88
Flash Point, Cleveland Open Cup, °C, ASTM D92	239	241
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.9	18.2
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	114	162

Property	MOBILGARD HSD 15W-40 CF-4	MOBILGARD HSD 20W-50 CF-4
Pour Point, °C, ASTM D97	-30	-27
Total Base Number, mgKOH/g, ASTM D2896	9.1	9.1

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2023

ExxonMobil Marine Limited

Ermyn Way

Leatherhead, Surrey

United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

**ExxonMobil**

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved