



EHC™ 20L

ExxonMobil Basestocks, Taiwan

產品說明

埃克森美孚的 EHC™ 基礎油專為在各種成品潤滑油應用環境中發揮效能而設。EHC™ 20L 是一種超輕中性基礎油，適用於各種低黏度潤滑油，包括用於汽車引擎、液壓和熱管理應用環境的潤滑油。選用 EHC™ 20L 可以減少使用 Group III 基礎油，同時滿足性能目標。埃克森美孚遵循嚴格的流程，確保一貫優質基礎油交貨情況，令客戶對其基礎油供應充滿信心。

特性與效益

優質的 EHC 20L 可使我們的客戶生產出高性能的潤滑油。主要特性包括：

- 出色的低溫性能和流動點
- 具有優秀氧化和熱穩定性的低芳香烴
- 可使配方滿足或超過行業/設備製造商要求的產品規格
- 顏色淺淡

規格

屬性	極限	標準方法 (a)	
石油賽波特比色計法	最小值	ASTM D156	10
黏度指數	最小值	ASTM D2270	85
100°C 條件下的運動黏度, mm ² /s	最小值 - 最大值	ASTM D445	2.1-2.6
閃火點, 克利夫蘭開口杯, °C	最小值	ASTM D92	150
流動點, °C	最大值	ASTM D97	-30
外觀	最小值 - 最大值	目視	清澈亮麗
40°C 條件下的運動黏度, mm ² /s	最小值	ASTM D445	7

附註 1: 產品在發佈時已經過認證，並符合指定的值。實際值可能會在指定測試方法的既定重現性範圍內出現偏差。

附註 2: 為確定是否符合規範，觀察值或計算值應根據 ASTM E 29 表示極限值的方法，將最後一位有效數字四捨五入至最接近的單位。

(a) 可使用替代測試方法代替標準測試方法來進行產品特性認證。

健康和 safety

如需了解本產品的健康與安全建議，請參閱物質安全資料表 (SDS): <http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有說明，否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標。

12-2022

ExxonMobil

3225 Gallows Road


Fairfax, VA 22037-001

1-800-662-4592

<http://www.exxonmobil.com>

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest range. Specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to or to supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

The ExxonMobil logo, featuring the word "ExxonMobil" in a bold, sans-serif font.A row of four logos: "Exxon", "Mobil", the "Esso" logo (a circle with "Esso" inside), and the "XTO" logo (with "EXXON MOBIL" written below it).

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved