



Mobil Super 1000 X4 20W-50

Mobil Passenger Vehicle Lube , United Arab Emirates

Extra High Performance Motor Oil

Product Description

The Mobil Super 1000 range of lubricants are premium mineral engine oils, designed to provide a high level of protection and performance.

Mobil Super 1000 X4 20W-50 is an extra high performance gasoline & Diesel motor oil that delivers engine protection and cleanliness. Mobil Super 1000 X4 20W-50 is recommended for use in a wide range of applications and operating conditions.

Features and Benefits

Mobil Super 1000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 X4 20W-50 provides:

- Good wear protection
- Good engine cleanliness
- Good high temperature protection

Applications

Mobil Super 1000 products have been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super 1000 for daily driving under a variety of driving conditions:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising

Specifications and Approvals

Mobil Super 1000 X4 20W-50 meets or exceeds the following industry specifications:	
API	SL

Mobil Super 1000 X4 20W-50 is recommended by ExxonMobil for use in applications requiring:	
API	CF

Typical Properties

Mobil Super 1000 X4 20W-50	Test Method	Unit	
SAE Grade			20W-50
Appearance	Visual		Bright and Clear
Viscosity @ 100°C	ASTM D445	cSt	18.9
CCS Viscosity @ -15°C	ASTM D5293	cP	8510

Mobil Super 1000 X4 20W-50	Test Method	Unit	
Sulfated Ash	ASTM D874	wt%	0.91
Total Base Number (TBN)	ASTM 2896	mg KOH/g	6.9
Flash Point	ASTM D92	°C	229
Pour Point	ASTM D97	°C	-24
Zinc	ASTM D4951	wt%	0.158

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request through your sales contract office, or via the Internet on <http://www.exxonmobil.com>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved