



Mobil Super™ Synthetic Technology 5W-30

Mobil Passenger Vehicle Lube , United Arab Emirates

Synthetic Technology Engine Oil

Product Description

Mobil Super™ Synthetic Technology 5W-30 is a synthetic technology engine oil designed to provide a high level of protection in gasoline vehicles, including the latest generation turbocharged gasoline fuel injected engines found in passenger cars, SUVs, and light commercial vans.

Features and Benefits

Mobil Super™ Synthetic Technology 5W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection to help extend engine life.

- Designed to provide very good wear protection, including timing chain elongation
- Helps to prevent LSPI occurrences in downsized gasoline engines operating under high heavy loads
- Helps to maintain engine cleanliness from sludge and carbon deposits
- Helps fuel economy in regards to ILSAC GF-6A / API Resource Conserving requirements
- Helps ensure compatibility with catalysts used in gasoline emission reduction systems

Applications

Mobil Super™ Synthetic Technology 5W-30 is recommended for use in many types of modern and prior design gasoline powered vehicles from American (Ford, GM, Chrysler...), Japanese (Toyota, Nissan, Mitsubishi, ...) and Korean (Hyundai, Kia, ...) car manufacturers.

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford WSS-M2C929-A
GM 6094M

This product meets or exceeds the requirements of:
API SJ
API SL
API SM
API SN
API SN PLUS
API SN PLUS RESOURCE CONSERVING

This product meets or exceeds the requirements of:

API SN Resource Conserving

API SP

API SP Resource Conserving

ILSAC GF-6A

Chrysler MS-6395

Ford WSS-M2C946-A

Ford WSS-M2C946-B1

FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Pour Point, °C, ASTM D97	-39
Viscosity Index, ASTM D2270	151
Density @ 15.6 C, g/ml, ASTM D4052	0.859
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	228

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved