



## Mobil™ Permazone 50/50 Prediluted Antifreeze & Coolant

Mobil Commercial Vehicle Lube , Argentina

Antifreeze & Coolant

### Product Description

Mobil™ Permazone 50/50 Prediluted Antifreeze & Coolant is a pre-mix solution for the cooling system that contains inhibitors that provide protection against freezing, overheating, rust and corrosion when used as recommended. Contains monoethylene glycol and inorganic corrosion inhibitors, IAT technology with stabilized silicates.

Mobil™ Permazone 50/50 Prediluted Antifreeze & Coolant is recommended for use without further dilution in all types of conventional cars and light trucks.

### Features and Benefits

Mobil™ Permazone 50/50 Prediluted Antifreeze & Coolant has the following features and benefits:

- The pre-mix cooling solution must be used without further dilution to complete the cooling system or as a refill for complete replacement of the used solution
- High boiling, low freezing point solution protects the system year-round providing excellent heat exchange and heat dissipation
- Contains corrosion inhibitors with IAT technology that provide adequate protection for all metals in the system, including the engine block and radiator
- Lubricates and protects the water pump preventing cavitation and erosion
- Extends the life of hoses, engine seals and thermostatic valve
- Greater stability during storage, which guarantees a shelf life of up to 5 years on shelves in the aftermarket

### Applications

Mobil™ Permazone 50/50 Prediluted Antifreeze & Coolant recommended drain interval for Passenger Vehicles is 3 years or 80,000 km, without adding additional loads of corrosion inhibitor additives in the pre-mix concentration.

In agricultural equipment and machinery drain interval recommended is 6,000 hours, without adding additional loads of corrosion inhibitor additives, as long as the system is cleaned before use. An annual additive level test is required to maintain the correct concentration throughout the period of use.

#### Meets or exceeds:

ASTM D3306  
ASTM D6210  
ASTM D4340  
ASTM D4985  
ABNT NBR 13705  
Caterpillar CAT ELC - EC - 1  
Chrysler MS7170 Sec. A&B 1-4  
Ford - Passenger Car and Light Truck  
Cummins CES 14603  
MTU MTL 5048  
Navistar MPAPS B-1  
Volvo / GM Heavy Trucks  
Mack Truck ELC Coolant  
TCM RP 329

### Properties and Specifications

Property	
Freeze Point (no dilution), C, ASTM D1177	-37
Density 20 C, g/ml, ASTM D1122	1.065
pH, of Finished Product, ASTM D1287	9
Foaming at 24 C, Time, s, ASTM D892	5
Foaming at 24 C, Volume, ml, ASTM D892	150
Boiling Point, C, ASTM D1120	108
Reserve Alkalinity, ml, ASTM D1121	5
Color, Visual	Green

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2023

Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8

CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved