



Mobilarma™ 200 Series

Mobil Industrial , Argentina

Rust Preventives

Product Description

Mobilarma™ 245 product is a premium quality rust preventive material designed to protect metal surfaces from rust and corrosion. It's formulated using light-bodied petroleum solvents with polar rust preventive, water displacement and fingerprint neutralising additives. These rust preventives are easy to apply and easy to remove making their application less man-power intensive. Mobilarma 245 is suited for the thin-film protection of finely finished parts between machining operations, including operations where water-soluble cutting and grinding fluids have been used. It is also suitable for use just before parts are packaged for storage or shipment, or to "dry" parts as a temporary protection until a heavier rust preventive can be applied.

Features and Benefits

The Mobilarma 245 provides exceptional protection of equipment during short and long-term storage. It's easy to apply and can be readily removed, where necessary, prior to placing equipment back in service. It can also be used to provide a rust and corrosion protective film to equipment and components for protection during shipment improving end customer satisfaction.

| Features | Advantages and Potential Benefits |
|-----------------------------|--|
| Outstanding Rust Protection | Protects equipment and components during non-use periods |
| | Reduces need for extensive cleanup procedures prior to placing equipment back in service |
| | Reduces component replacement costs |

Applications

- Protection of equipment during storage or while temporarily out of service
- Coating of equipment in preparation for shipment

Properties and Specifications

| Property | 245 |
|---|------|
| API Gravity, °API, ASTM D4052 | 43 |
| ASTM Color, ASTM D1500 | |
| Calcium, mass%, ASTM D4951 | |
| Density @ 60 F, lb/gal, CALCULATED | 6.75 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

COSAN LUBRICANTES S.R.L

Tucumán 1 – Piso 4º

CP 1049 – CABA – Buenos Aires, Argentina

0800 345 7954

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved