Mobil

Mobil Super Moto Chain Lube

Mobil Passenger Vehicle Lube , Argentina

Product Description

Mobil Super Moto Chain Lube is an oil, available in spray form, developed to lubricate motorcycle chains.

Features and Benefits

Mobil Super Moto Chain Lube has superior wear protection and excellent penetration into the chain links, lubricating them efficiently. Its adhesiveness to metal parts is adequate, without accumulation of dust and without splashing.

Applications

Recommended for lubrication of motorcycle chains. Recommended for general chain lubrication.

Properties and Specifications

Property	
Flash Point, °C, ASTM D92	212
Appearance, Visual	Clear & Bright
Density 20/4C, g/ml, ASTM D891	0.89
Humidity, wt %, LAB/MA/049	NIL
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	140
Color, Visual	Dark Brown

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2021 Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8 CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All primary not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intenoverride or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

