



Mobil Super 3000 Formula D1 0W-20

Mobil Passenger Vehicle Lube , Argentina

Full Synthetic Motor Oil

Product Description

Mobil Super 3000 Formula D1 0W-20 motor oils is a full synthetic formulated with the new GF-6 and API SP specifications which is a high performance formulation that outperform our conventional and synthetic blend oils and is designed to provide long engine life and outstanding protection in vehicles of all ages.

Mobil Super 3000 Formula D1 0W-20 motor oil protect critical engine parts from lubricant related failures for up to 12,000 kilometers or your vehicle's OEM recommended oil change interval, whichever is longer*, and meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.

Features and Benefits

Mobil Super 3000 Formula D1 0W-20 motor oil is a full synthetic, high performance formulations that outperform our conventional/synthetic blend oils and are designed to provide long engine life and outstanding protection in vehicles of all ages.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Meets or exceeds the latest industry specifications	OEM warranty protection
Protects up to 400°F/204°C	Helps prevent oil breakdown during extended high temperature operation
High performance additives	Protects against wear and combat sludge and deposits
Warranty	Limited Warranty* offers protection for up to 12,000 kilometers or your vehicle's recommended oil change interval, whichever is longer
Full synthetic formula	Easy starting and rapid oil circulation during cold starts to protect critical engine parts
Tested, proven engine protection	Helps extend engine life
Engine cleanliness	Fuel economy

Applications

Mobil Super 3000 Formula D1 0W-20 motor oil is recommended by ExxonMobil for all types of modern gasoline/ethanol powered vehicles, including high-performance turbocharged, supercharged, multi-valve, fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

Mobil Super 3000 Formula D1 0W-20 meets and exceeds requirements of API SP specification

- Mobil Super 3000 Formula D1 0W-20 motor oil meet warranty requirements where an American Petroleum Institute (API) certified oil is specified.
- Mobil Super 3000 Formula D1 0W-20 oil is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

Specifications and Approvals

This product has the following approvals:

GM dexos1:GEN2 Licensed

This product meets or exceeds the requirements of:

API SM

API SN

API SN PLUS

API SN Resource Conserving

API SN PLUS RESOURCE CONSERVING

API SP

API SP Resource Conserving

ILSAC GF-6A

Chrysler MS-6395

Ford WSS-M2C947-A

Ford WSS-M2C947-B1

FORD WSS-M2C962-A1

Properties and Specifications

Property	
Grade	SAE 0W-20
Pour Point, °C, ASTM D97	-39
Cold-Cranking Simulator, Apparent Viscosity @ -35 C, mPa.s, ASTM D5293	4850
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	43
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.2
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	18500
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Density @ 15.6 C, g/ml, ASTM D4052	0.8451

Property	
Viscosity Index, ASTM D2270	171

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8

CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved