



## Mobil Delvac™ Super 1400E 15W-40

Mobil Commercial Vehicle Lube , Austria

High Performance Diesel Engine Oil

### Product Description

Mobil Delvac™ Super 1400E 15W-40 is a high performance diesel engine oil that provides protection for diesel engines operating under severe service conditions for both on- and off-highway applications. Mobil Delvac Super 1400E 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries

### Features and Benefits

Thermal and oxidation stability Helps to control sludge build-up and deposits

TBN reserve Helps to control deposits

Stay-in-grade shear stability Helps to reduce oil consumption and to provide wear protection

Excellent detergency/ dispersancy Helps to protect and to maintain engines clean

Component compatibility Long gasket and seal life

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Helps to control sludge build-up and deposits
TBN reserve	Helps to control deposits
Stay-in-grade shear stability	Helps to reduce oil consumption and to provide wear protection
Excellent detergency/ dispersancy	Helps to protect and to maintain engines clean
Component compatibility	Long gasket and seal life

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers in line with owner manual recommendations
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

### Specifications and Approvals

<b>This product has the following builder approvals:</b>
MTU Oil Category 1

<b>This product is recommended by ExxonMobil for use in applications requiring:</b>
---

**This product is recommended by ExxonMobil for use in applications requiring:**

RENAULT TRUCKS RD

RENAULT TRUCKS RD-2

VOLVO VDS-2

API CF

API CF-4

API CG-4

**This product meets or exceeds the requirements of:**

API SJ

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, °C, ASTM D92	230
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	106
Pour Point, °C, ASTM D97	-27
Total Base Number, mgKOH/g, ASTM D2896	9.7
Viscosity Index, ASTM D2270	140
Specific Gravity, 15 C/15 C, ASTM D4052	0.881
Cold-Cranking Simulator, Apparent Viscosity @ -20 C, mPa.s, ASTM D5293	6150

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)  
 POLDERDIJKWEG  
 B-2030 Antwerpen

## Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

The ExxonMobil logo is displayed in white text on a dark background.A row of four logos: Exxon, Mobil, Esso, and XTO Energy, all in white on a dark background.

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved