



Chainsaw Oil

Mobil Industrial , Austria

Product Description

Chainsaw Oil is specifically developed for the lubrication of chain and guide bars of modern chain saws. Selected mineral base oils are combined with special additives to provide good protection against wear, rust and corrosion. Chainsaw Oil has good low temperature flow properties which makes it suitable for outside applications even during the winter season.

Features and Benefits

Features	Advantages and Potential Benefits
Good adherence to metal surfaces	Stays well in place on saw chains and guide bars and ensures optimum component lifetime
Excellent protection against wear, rust and corrosion	Contribution toward increased chain and guide bar life and reduced maintenance costs as wear related failures are reduced
Low pour point	Ensures flow ability even at low operating temperatures for higher efficiency

Applications

Chainsaw Oil can be used in hand-held or machine operated chain saws as specified by the manufacturer. It is suitable for lubrication of chains, slideways and guides in industrial applications, where a lubricant with good adherence, protection against wear, rust and corrosion and a low pour point is required.

Properties and Specifications

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11
Pour Point, °C, ASTM D97	-24

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)
 POLDERDIJKWEG
 B-2030 Antwerpen
 Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved