



## Mobil DTE™ PM Excel Series

Mobil Industrial , Austria

Paper Machine Lubricant

### Product Description

Mobil DTE™ PM Excel is a multi-functional paper machine oil for use in wet end, dry end, press sections and calender circulation oil systems. The fluid has formulated with select high-quality base oils and a proprietary advanced technology additive system carefully balanced to achieve high performance standards provide maximum protection of gears and bearings operating under severe conditions.

### Features and Benefits

Mobil DTE PM Excel has the following potential benefits:

- Excellent anti-wear protection of bearings and gears of system components using various metallurgy help extend component life
- Ultra keep clean properties reduce system deposits and sludge help protect equipment and extend equipment life, which can reduce maintenance costs and in total system performance
- Exceptional thermal / oxidation stability help reduce maintenance downtime and costs by contributing to system cleanliness and deposit reduction, which can long oil and filter life
- Meets wide range of equipment requirements which helps avoid risk of mis-application and enable potential inventory reduction
- High level rust and corrosion protection which can help improve production capacity

### Applications

- Lubrication of the wet end, press section, calender applications and dry end, including in Voith and Metso (Valmet) paper machines
- Application involving circulation systems operating over a wide temperature range
- Systems that must be started and brought on line quickly
- Circulation systems' lubricating gears and bearings

### Specifications and Approvals

| <b>This product is recommended for use in applications requiring:</b> | <b>150</b> | <b>220</b> |
|---|------------|------------|
| Valmet RAU4L00659_07  | X          | X          |
| Valmet RAUAH02724_01  | X          | X          |
| Voith Paper VS 108 5.3.1 2021-10 (wet end)                            | X          |            |
| Voith Paper VS 108 5.3.2 2021-10 (dry end)                            |            | X          |
| Voith Paper VS 108 5.3.3 2021-10 (off-line coaters)                   | X          |            |
| Voith Paper VS 108 5.3.4 2021-10 (hydraulic roll)                     | X          |            |
| Voith Paper VS 108 5.3.5 2021-10 (shoe press)                         | X          | X          |
| Voith Paper VS 108 5.3.6 2021-10 (winder)                             |            | X          |

| <b>This product meets or exceeds the requirements of:</b> | <b>150</b> | <b>220</b> |
|---|------------|------------|
|   |            |            |

| This product meets or exceeds the requirements of: | 150 | 220 |
|--|-----|-----|
| DIN 51517-3:2018-09                                | X   | X   |
| DIN 51524-2:2017-06                                | X   |     |

### Properties and Specifications

| Property  | 150     | 220     |
|---|---------|---------|
| Grade   | ISO 150 | ISO 220 |
| Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130       | 1A      | 1A      |
| Demulsibility, Time to 3 mL Emulsion, 82 C, min, ASTM D1401 | 10      | 10      |
| FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1        | +12     | +12     |
| Flash Point, Cleveland Open Cup, °C, ASTM D92               | 264     | 278     |
| Foam, Sequence I, Stability, ml, ASTM D892                  | 0       | 0       |
| Foam, Sequence I, Tendency, ml, ASTM D892                   | 0       | 0       |
| Foam, Sequence II, Stability, ml, ASTM D892                 | 0       | 0       |
| Foam, Sequence II, Tendency, ml, ASTM D892                  | 0       | 0       |
| Foam, Sequence III, Stability, ml, ASTM D892                |         | 0       |
| Foam, Sequence III, Tendency, ml, ASTM D892                 |         | 0       |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445  | 14.5    | 18.7    |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445   | 145     | 214     |
| Pour Point, °C, ASTM D97                                    | -18     | -15     |
| Rust Characteristics, Procedure A, ASTM D665                | PASS    |         |
| Rust Characteristics, Procedure B, ASTM D665                | PASS    | PASS    |
| Specific Gravity @ 15.5 C, ASTM D1298                       |         | 0.894   |
| Specific Gravity, 15.6 C/15.6 C, ASTM D1298                 | 0.888   |         |
| Viscosity Index, ASTM D2270                                 | 96      | 97      |

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

06-2023

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)  
POLDERDIJKWEG

B-2030 Antwerpen  
Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved