



Mobil Super™ 3000 Formula M 5W-30

Mobil Passenger Vehicle Lube , Austria
Mobil passenger-vehicle-lube , United Kingdom High performance engine oil

Product Description

Mobil Super 3000 Formula M 5W-30 is a high-performance engine oil primarily intended for use in Mercedes Benz (MB) vehicles where a product for extended : intervals (Long Life) is required.

Features and Benefits

- Mobil Super 3000 Formula M 5W-30 provides the following features and benefits:
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
 - Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation throughout the engine.
 - Provides excellent engine protection from wear and sludge.

Applications

Mobil Super 3000 Formula M 5W-30 has been developed to meet the highest specifications for Mercedes Benz gasoline and Diesel engine passenger cars. Its Full SAPS (high ash) formulation provides the extra protection needed for long drain servicing of engines without particle filters or operating in regions with high fuels.

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.3
MB-Approval 229.5

Properties and Specifications

Property	
Grade	SAE 5W-30
Pour Point, °C, ASTM D97	-42
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	12.1
Viscosity Index, ASTM D2270	159
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	74.8
Flash Point, Cleveland Open Cup, °C, ASTM D92	240

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved