



Mobil Super™ 3000 0W-16

Mobil Passenger Vehicle Lube , Austria

Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 0W-16 is an ultra-low viscosity, fully synthetic engine oil developed to help improve engine efficiency and provide outstanding wear protection in highly efficient, internal combustion and hybrid vehicles.

Mobil Super 3000 0W-16 addresses emerging engine technology where vehicle manufacturers strive to optimise fuel economy. It is the oil of choice for select gasoline and hybrid engines from Honda, Lexus and Toyota which are designed to operate at their optimum with 0W-16 oils.

Features and Benefits

Mobil Super 3000 0W-16 is designed to help provide long engine life and outstanding protection against sludge, engine rust and corrosion under severe operating conditions and provide optimum viscosity and fluidity across a broad range of temperatures.

- Designed for modern and highly efficient gasoline and hybrid engines
- Meets or exceeds latest ILSAC and API industry standards
- Protects against low-speed pre-ignition for gasoline engines with direct injection and turbocharging
- Outstanding wear protection, helps extend engine life
- Permits operation at elevated temperatures without oxidative oil thickening and oil breakdown
- Allows easy cold-weather starting and reduced engine warm-up time to protect critical engine parts

Applications

Mobil Super 3000 0W-16 is designed for gasoline fueled automobiles where a SAE 0W-16 viscosity is recommended by the car builder and is suitable for select gasoline vehicles and hybrids from Toyota, Lexus and Honda. Mobil Super 3000 0W-16 meets or exceeds the American Petroleum Institute's latest SP requirements and the novel ILSAC GF-6B category for low viscosity oils which hold resource conserving credentials.

Note GF-6B category, contrary to GF-6A category, is not backward compatible with previous ILSAC categories (GF-1 through GF-5) therefore Mobil Super 3000 0W-16 should be used only when GF-6B / 0W-16 spec is recommended in the owner's manual.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SP
ILSAC GF-6B
API SJ
API SL
API SM
API SN

This product meets or exceeds the requirements of:

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SP Resource Conserving

Properties and Specifications

Property	
Grade	SAE 0W-16
Density @ 15 C, g/ml, ASTM D1298	0.831
Flash Point, Cleveland Open Cup, °C, ASTM D92	238
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	38.2
Pour Point, °C, ASTM D97	-54
Viscosity Index, ASTM D2270	160

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2021

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved