



Mobil Pyrotec™ HFD 46B

Mobil Industrial , Australia

Fire-Resistant Hydraulic Fluid

Product Description

Mobil Pyrotec™ HFD 46B is a high performance phosphate ester self-extinguishing fire resistant hydraulic fluid. Mobil Pyrotec HFD 46B is TXP-free.

Mobil Pyrotec HFD 46B has been evaluated in stringent tests for fire resistance such as the ISO 20823 manifold ignition test. Compared to other types of synthetic or mineral fire resistant fluids, Mobil Pyrotec HFD 46B shows a much higher ignition temperature (greater than 700°C) and is very difficult to ignite. If ignited, the flame will self-extinguish.

Mobil Pyrotec HFD 46B is formulated from specially purified phosphate base stocks and additives providing improved oxidation stability and lubrication properties. Physical properties such as foaming, air release and demulsibility are controlled to meet the limits specified by turbine manufacturers.

Features and Benefits

| Features | Advantages and Potential Benefits |
|---------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| High ignition temperature and self-extinguishing capability, approved by FM Approvals | Preferred choice in applications where fire safety is critical |
| TXP-free formulation | Compliance with future safety, health and environment regulations |
| Excellent oxidation resistance | Helps to extend oil life |
| Excellent anti-wear properties | Helps to extend component life |

Applications

Mobil Pyrotec HFD 46B is recommended for use in applications where fire safety is critical, such as:

- Electro-hydraulic governor control systems of steam turbines, especially where a high performance fluid is required,
- Hydraulic and oil circulation systems operating in conditions subject to fire hazards,
- Other applications such as gas turbines, turbo-compressors, reactor coolant pumps and generators.

Please note that Mobil Pyrotec HFD 46B is fully compatible with Mobil Pyrotec HFD 46.

Special precautions should be taken when using Mobil Pyrotec HFD 46B regarding:

- System operating temperatures: normal system temperature should be between 50 and 65°C to avoid water condensation and local spot temperatures should be kept below 150°C,
- Flushing procedure when replacing petroleum oils, conventional soluble emulsions, water in oil emulsions or water glycol fluids,
- Compatibility with elastomers (for example, Mobil Pyrotec HFD 46B is not recommended for use with Neoprene, nitrile and silicon materials but compatible with seals and hose materials such as butyl rubber and Viton),
- Compatibility with paints, enamels and varnishes (for example, Mobil Pyrotec HFD 46B is not recommended for acrylic, latex and phenolic resin paints

but compatible for example with epoxy type paints).

Please contact your your ExxonMobil representative for further details.

Specifications and Approvals

| This product has the following approvals: |
|--------------------------------------------------|
| FM Global Approvals Class 6930 |
| Siemens TLV 9012 02 |
| Siemens TLV 9012 03 |
| Mitsubishi Power Ltd MS04-MA-CL004(Rev.6) |

| This product meets or exceeds the requirements of: |
|-----------------------------------------------------------|
| GE Power GEK 46357H |

Properties and Specifications

| Property | |
|---------------------------------------------------------|---------------|
| Grade | ISO 46 |
| Kinematic Viscosity @ 40C, mm ² /s, ISO 3104 | 43.5 |
| Flash Point, Cleveland Open Cup, °C, ISO 2592 | 258 |
| Foam Sequence II, Tendency, ml, ISO6247 | 15 |
| Foam Sequence II, Stability, ml, ISO6247 | 0 |
| Water Separability, min, ISO 6614 | 5 |
| Total Acid Number, mgKOH/g, ISO 6619 | 0.04 |
| Volume Resistivity 20C, MOhm.m, IEC 60247 | 340 |
| Water, wt %, ISO 760 | 0.06 |
| Chlorine, ppm, IP 510/04 | 5 |
| Appearance, Visual | Clear |
| Particle Count, Rating, ISO 4406 | -/15/12 (max) |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2022

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved