



**Mobil 1™ 5W-30**  
Mobil Passenger Vehicle Lube , Australia  
Advanced Full Synthetic Engine Oil

**Product Description**

Mobil 1™ Triple Action Power advanced full synthetic engine oil delivers outstanding engine Performance, Protection, and Cleanliness.

**Features and Benefits**

Why these matter for your engine:

- **PERFORMANCE:** Reduces the stress of daily wear and harsh conditions for longer engine life.
- **PROTECTION:** Guards against extreme temperatures to prevent breakdowns.
- **CLEANLINESS:** Prevents buildup of contaminants and sludge for a cleaner engine.

Mobil 1™ Triple Action Power is feature packed to:

- **PERFORM:** Keeps your engine running like new.
- **PROTECT:** 10X\* better protection for high temperatures.
- **CLEAN:** Fights sludge with active cleaning agents.

\*Based on Sequence IIIH, against API SP specification

**Applications**

Mobil 1™ Triple Action Power is suitable for use in petrol, diesel, and hybrid vehicles.  
Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle.

**Specifications and Approvals**

<b>This product has the following approvals:</b>
HONDA/ACURA HTO-06
<b>This product is recommended for use in applications requiring:</b>
Ford WSS-M2C929-A
Ford WSS-M2C946-A
Ford WSS-M2C946-B1
FIAT 9.55535-CR1
<b>This product meets or exceeds the requirements of:</b>

**This product meets or exceeds the requirements of:**

FORD WSS-M2C961-A1

Chrysler MS-6395

CHRYSLER MS-13340

API SP Resource Conserving

API SP

API SN PLUS

API SN

API SM

ILSAC GF-6A

ACEA A5/B5

ACEA C2

**Properties and Specifications**

Property	
Grade	SAE 5W-30
Total Base Number, mgKOH/g, ASTM D2896	9.2
Ash, Sulfated, mass%, ASTM D874	0.76
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	61
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 <sup>6</sup> sec <sup>-1</sup> , mPa.s, ASTM D4683	3
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.3
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	13700
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Density @ 15.6 C, g/ml, ASTM D4052	0.852
Viscosity Index, ASTM D2270	157

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006  
+61 3 8633 8444  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com). ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved