



Mobil Super™ 2000 Formula P 10W-40

Mobil Passenger Vehicle Lube , Australia

Mobil passenger-vehicle-lube

Product Description

Mobil Super 2000 Formula P 10W-40 is an enhanced premium semi-synthetic engine oil designed to provide excellent level of protection and performance.

Features and Benefits

Mobil Super 2000 Formula P 10W-40 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection

Applications

Mobil Super 2000 Formula P 10W-40 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines
- Stop and Go City Driving

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
PSA B712300
VW 501 01
VW 505 00

This product is recommended for use in applications requiring:

API CF

MB 229.1

This product meets or exceeds the requirements of:

API SN

API SN PLUS

ACEA A3/B3-16

ACEA A3/B4-16

Properties and Specifications

Property	
Grade	SAE 10W-40
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	26200
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	97
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.4
Density @ 15.6 C, g/ml, ASTM D4052	0.866
Total Base Number, mgKOH/g, ASTM D2896	10.7
Viscosity Index, ASTM D2270	154
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Pour Point, °C, ASTM D97	-33
Ash, Sulfated, mass%, ASTM D874	1.2

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved