



Mobil Super™ 3000 Formula D1 0W-20

Mobil Passenger Vehicle Lube , Australia

Mobil passenger-vehicle-lube

Product Description

Mobil Super™ 3000 Formula D1 0W-20 is a synthetic motor oil, which provides excellent high temperature protection even under severe operating conditions. Mobil Super 3000 is designed to help provide long engine life and outstanding protection in vehicles of all ages. Mobil Super 3000 provides outstanding protection against sludge, engine rust and corrosion under severe and low temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super 3000 Formula D1 0W-20 meets or exceeds ILSAC GF-6A and API SP. Those claims are backward compatible with earlier performance levels such as API SN, SM, SL, and SJ and previous ILSAC categories.

Mobil Super 3000 Formula D1 0W-20 is approved against GM dexos1™ Gen 2 under the license D10164GJ015.

Features and Benefits

Helps extend engine life

Outstanding wear protection for vehicles of all ages

Excellent high temperature protection to help keep engines cool

Permits extended operation at elevated temperatures (up to 400° F) without oxidative oil thickening and oil breakdown

Helps control oil consumption and loss

Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts

Meets or exceeds the latest industry specifications

Applications

Mobil Super 3000 Formula D1 0W-20 is recommended for gasoline fueled automobiles where a 0W-20 viscosity is required. It meets or exceeds the requirements of API SP and ILSAC GF-6A.

Specifications and Approvals

This product has the following approvals:

GM dexos1:GEN2 Licensed

This product meets or exceeds the requirements of:

API SP

API SP Resource Conserving

ILSAC GF-6A

Chrysler MS-6395

This product meets or exceeds the requirements of:

Ford WSS-M2C947-A

Ford WSS-M2C947-B1

FORD WSS-M2C962-A1

Properties and Specifications

Property	
Grade	SAE 0W-20
Pour Point, °C, ASTM D97	-45
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	43
Total Base Number, mgKOH/g, ASTM D2896	8.2
Viscosity Index, ASTM D2270	171
Density @ 15.6 C, g/ml, ASTM D4052	0.846
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	26900
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	2.6
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	231

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved