



Mobil Delvac Modern™ Light Commercial F 0W-30

Mobil Commercial Vehicle Lube , Azerbaijan

High Performance Light Duty Diesel Engine Oil

Product Description

Mobil Delvac Modern™ Light Commercial F 0W-30 is an advanced synthetic technology engine oil developed to meet the Ford requirement "WSS-M2C950-A". It is designed to help provide long engine life and outstanding protection for diesel engines operating in severe driving conditions, typically encountered in city operations.

This product is designed for Ford light-duty commercial vehicles but ExxonMobil also recommends it for vans which need to meet requirements of ACEA A5/B5 and ACEA C2.

Features and Benefits

Mobil Delvac Modern Light Commercial F 0W-30 meets the technical requirements according to Ford's standard WSS-M2C950-A, based on the OEM engine tests.

The usage of this product is meant to provide the following benefits:

- Increased fuel economy 1
- Extended life of diesel particulate filter 2
- Enhanced lower temperature properties 3

1. based on FORD WSS-M2C950-A 0W-30 spec compared to the FORD WSS-M2C913-D 5W-30 oil

2. based on ACEA C2 requirements

3. based on SAE 0W-30 spec compared to SAE 5W-30 oil

Applications

ExxonMobil recommends Mobil Delvac™ Light Commercial Vehicle F 0W-30 for demanding driving conditions:

- Ford Light Commercial Vehicles for engines requiring WSS-M2C950-A
- Light Commercial Vehicles requiring ACEA A5/B5 and ACEA C2
- Normal to occasionally severe operating conditions (including city driving conditions)

Owner's manual should be consulted for recommended viscosity grades and specification.

Specifications and Approvals

This product meets or exceeds the requirements of:

ACEA A5/B5

ACEA C2

FORD WSS-M2C950-A

Properties and Specifications

Property	
Grade	SAE 0W-30
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	45
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.6
Density @ 15.6 C, g/ml, ASTM D4052	0.84
Total Base Number, mgKOH/g, ASTM D2896	8
Cold-Cranking Simulator, Apparent Viscosity @ -35 C, mPa.s, ASTM D5293	5100
Noack Volatility, mass%, ASTM D5800	12
Ash, Sulfated, mass%, ASTM D874	0.77
Viscosity Index, ASTM D2270	204
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved