



Mobil Super™ 1000 X1 20W-50

Mobil Passenger Vehicle Lube , Bosnia

Mobil Passenger Engine Oil

Product Description

The Mobil Super™ 1000 range of lubricants are premium mineral engine oils, designed to provide a high level of protection and performance.

Features and Benefits

Mobil Super 1000 products are industry tested so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 X1 provides:

- Good wear protection
- Good engine cleanliness
- Good high temperature protection

Applications

Mobil Super 1000 products have been formulated for use in nearly all vehicles. Mobil Super 1000 is suitable for:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Mobil Super 1000 X1 20W-50 is also suitable for use in LPG vehicles.

ExxonMobil particularly recommend Mobil Super 1000 for daily driving under normal conditions. Always consult your owner's manual to check recommended vi: grade and specifications for your particular vehicle.

Specifications and Approvals

| |
|---|
| This product has the following approvals: |
| MB-Approval 229.1 |
| VW 501 01 |
| VW 505 00 |

| |
|--|
| This product is recommended for use in applications requiring: |
| API CF |

| |
|--|
| This product meets or exceeds the requirements of: |
| API SJ |
| API SL |

| |
|--|
| This product meets or exceeds the requirements of: |
| API SM |
| API SN |
| API SN PLUS |
| ACEA A3/B3 |

Properties and Specifications

| Property | |
|---|------------|
| Grade | SAE 20W-50 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 20.4 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 181 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.886 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 255 |
| Pour Point, °C, ASTM D97 | -27 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XT

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved