



## SOMENTOR 44 AND 53

Mobil Industrial , Belgium

Rolling Oils

### Product Description

Somentor 44 is a low sulfur containing mineral rolling oil. The narrow distillation range and the special production procedure gives the product good evaporation properties and excellent oxidation stability.

Somentor 53 is a highly refined mineral oil cut designed for use as rolling oil.

### Features and Benefits

Somentor 44

- Balanced boiling range allows high reductions per pass and provides acceptable annealing properties.
- Versatile product for a wide range of applications.

Somentor 53

- Good oxidation stability to prevent sludging.
- Excellent behaviour in bright anneal.

### Applications

Somentor 44 is particularly suited for cold rolling of aluminium and other metals.

If necessary Somentor 44 is blended with suitable additives, such as Wyrrol grades, to formulate fully compounded roll oils to meet the needs of the individual mill operations.

Somentor 53 is used primarily as a base oil for blending compounded roll oils for cold rolling of stainless steel, steel, copper and copper alloys. In some special application where no additives are required it may also be used directly.

### Properties and Specifications

Property	44	SOMENTOR 53
Appearance, AMS 1738	Clear & bright	Clear & bright
Copper Strip Corrosion, Rating, ASTM D130	<1	
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130		<1
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	<5	7.1

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2021

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical BV

Polderdijkweg

B-2030 Antwerpen

Automotive products: 0800 80634

Industrial products: 0800 80635

Fax: 0800 80648

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved