



Mobil Super™ 3000 Formula P 0W-30

Mobil Passenger Vehicle Lube , Belgium

High Performance Motor Oil

Product Description

Mobil Super 3000 Formula P 0W-30 is especially developed to meet the Peugeot Citroën latest requirements, Peugeot Citroën Automobiles B71 2312. Mobil Super 3000 Formula P 0W-30 shows Fuel Economy benefits vs. current Mobil Super 3000 Formula P 5W-30. Mobil Super 3000 Formula P 0W-30 is a low ash high performance motor oil designed to help prolong the life and maintain the efficiency of the car exhaust Emission Reduction Systems in both Diesel and gasoline powered automobiles.

Features and Benefits

Mobil Super 3000 Formula P 0W-30 delivers excellent high and low temperature wear-protection and engine cleanliness.

Key features and benefits:

- Low Ash, low phosphorous and low sulfur formulation helping to prolong the life and maintain the efficiency of the Emission Reduction Systems in both Diesel and Gasoline powered engines.
- Fully compatible with most Diesel Particulate Filters and Catalytic Convertors.
- Help achieve fuel economy (as per ACEA C2).
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine and electrical system protection.
- High performance wear-protection.
- Active cleaning agents reducing deposits and sludge build-up to enable long and clean engine life.

Applications

Mobil Super 3000 Formula P 0W-30 can be used for all Diesel and gasoline engines requiring Peugeot Citroën B71 2312.

Specifications and Approvals

|                                           |
|-------------------------------------------|
| This product has the following approvals: |
| PSA B71 2312                              |
| PSA B71 2302                              |

|                                                    |
|----------------------------------------------------|
| This product meets or exceeds the requirements of: |
| FIAT FIAT 9.55535-GS1                              |
| ACEA C2                                            |

Properties and Specifications

| Property                                      |           |
|-----------------------------------------------|-----------|
| Grade                                         | SAE 0W-30 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 9.7       |

| Property                                      |      |
|-----------------------------------------------|------|
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 51.8 |
| Density @ 15.6 C, g/ml, ASTM D4052            | 0.84 |
| Pour Point, °C, ASTM D97                      | -42  |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 234  |
| Ash, Sulfated, mass%, ASTM D874               | 0.5  |
| Phosphorus, mg/kg, ASTM D5185                 | 0.08 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024  
ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical BV  
Polderdijkweg  
B-2030 Antwerpen

Automotive products: 0800 80634  
Industrial products: 0800 80635  
Fax: 0800 80648

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil





© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved