



Mobil Super™ 3000 XE 5W-30

Mobil Passenger Vehicle Lube , Belgium

Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super 3000 XE 5W-30 is a high performance, low ash engine oil designed to help prolong engine life and maintain the efficiency of the exhaust emission red systems in both diesel and gasoline powered passenger cars, light commercial vehicles and vans.

This product is recommended for use in Mercedes vehicles and a wide range of European cars and light-duty commercial vehicles with oil specifications built ACEA C3 and/or API SN industry baseline.

Features and Benefits

Mobil Super 3000 XE 5W-30 helps to maintain the efficiency of the exhaust emission reduction systems in both diesel and gasoline vehicles.

- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Long term engine protection from wear and sludge and deposit build-up
- Suitable for use in both gasoline and diesel engine passenger car and light commercial vehicles

Applications

Mobil Super 3000 XE 5W-30 has been developed to meet the latest specifications for engine oils required by major car manufacturers and is compatible with the Gasoline and Diesel Particulate Filters and catalytic converters.

Mobil Super 3000 XE 5W-30 is specially recommended by ExxonMobil for use in:

- Mercedes passenger cars and light commercial vehicles or vans. This motor oil is also recommended for many Volkswagen, Opel and Ford passenger car commercial vehicles or vans requiring ACEA C3 and/or API SN
- Gasoline and Diesel with Diesel Particulate Filters (DPF) & Catalytic Convertors.
- Normal to occasionally severe operating conditions including city driving conditions.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
GM DEXOS2 - SF
MB-Approval 229.31
VW 505 00
VW 505 01
MB-Approval 229.51

This product has the following approvals:

MB-Approval 229.52

This product is recommended for use in applications requiring:

API CF

FORD WSS-M2C917-A

GM-LL-A-025

GM-LL-A-025

This product meets or exceeds the requirements of:

ACEA C3

API SM

API SL

API SN

Properties and Specifications

Property	
Grade	SAE 5W-30
Ash, Sulfated, mass%, ASTM D874	0.8
Density @ 15 C, g/ml, ASTM D4052	0.85
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	68
Phosphorus, mass%, ASTM D4951	0.08
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2024

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical BV

Polderdijkweg

B-2030 Antwerpen

Automotive products: 0800 80634

Industrial products: 0800 80635

Fax: 0800 80648

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved