



Mobil Super 3000 Formula V 0W-30

Mobil Passenger Vehicle Lube , Belgium

High Performance Engine Oil

Product Description

Mobil Super 3000 Formula V 0W-30 is a low ash, high performance engine oil for diesel and gasoline powered European vehicles, designed for extended drain protection and to help maintain the efficiency of car Emission Reduction Systems.

This engine oil has been developed specifically for servicing VAG vehicles (VW, Audi, Porsche).

Features and Benefits

Mobil Super 3000 Formula V 0W-30 delivers excellent high and low temperature wear-protection and engine cleanliness.

Key features and benefits:

- Compatible with Diesel Particulate Filters and Catalytic Convertors. Low ash, low phosphorous and low sulfur formulation helps prolong the life and maintain the efficiency of the emission reduction systems in both Diesel and Gasoline powered engines.
- Excellent low temperature capabilities for reliable cold weather starting allows fast engine and electrical system protection.
- High performance wear-protection conferred by high oil film strength and additive system.
- Active cleaning agents reducing deposits and sludge build-up enable long and clean engine life.
- Suitable for long life servicing.

Applications

Mobil Super 3000 Formula V 0W-30 is recommended for modern turbocharged and direct injection gasoline or diesel engines equipped with exhaust treatment systems (Euro 6, Euro 5 and Euro 4 compliant). It carries VW 504 00 / VW 507 00 and Porsche C30 approvals for usage in VAG vehicles from 2000 onwards specifying oil with extended service intervals (30,000km / 2 years as per car owner's manual).

Mobil Super 3000 Formula V 0W-30 is also recommended for Japanese and Korean vehicles specifying a low ash ACEA C3 / SAE xW-30 engine oil.

Specifications and Approvals

This product has the following approvals:
VW 504 00
VW 507 00
Porsche C30

This product meets or exceeds the requirements of:
ACEA C3

Properties and Specifications

Property	

Property	
Grade	SAE 0W-30
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	61.3
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Density @ 15 C, g/ml, ASTM D1298	0.844
Ash, Sulfated, mass%, ASTM D874	0.8
Pour Point, °C, ASTM D97	-49
Phosphorus, mass%, ASTM D4951	0.08
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.2

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical BV

Polderdijkweg

B-2030 Antwerpen

Automotive products: 0800 80634

Industrial products: 0800 80635

Fax: 0800 80648

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved