



Mobil Extra 4T 10W40

Mobil Passenger Vehicle Lube , Belgium

Superior Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Extra 4T is a high performance, semi-synthetic blend technology four-stroke motorcycle engine oil developed to provide boosted engine cleanliness and protection for all types of motorcycles and operation.

Features and Benefits

Mobil Extra 4T combines a unique blend of high quality mineral and synthesised hydrocarbon baseoils together with an advanced additive system to provide excellent engine cleanliness, wear protection and effective corrosion prevention. Key features and benefits include:

| Features | Advantages and Potential Benefits |
|--|--|
| Excellent wear protection | Longer engine component and overall engine life |
| Good thermal , oxidation stability and deposit control | Cleaner running engines resulting in smooth flawless operation |
| Excellent corrosion protection properties | Longer life of valve train and bearing components |
| Enhanced low temperature properties | Easier cold weather starting, longer electrical system life |

Applications

Mobil Extra 4T is specifically recommended for lubrication of all types of four-stroke motorcycle engines, where the latest industry standard qualities are required.

Specifications and Approvals

| This product meets or exceeds the requirements of: |
|--|
| API SJ |
| JASO MA2 |

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 10W-40 |
| Ash, Sulfated, mass%, ASTM D874 | 0.9 |
| Density @ 15.6 C, g/ml, ASTM D4052 | A |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.4 |

| Property | |
|---|-----|
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 98 |
| Pour Point, °C, ASTM D97 | -30 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | A |
| Viscosity Index, ASTM D2270 | 157 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical BV

Polderdijkweg

B-2030 Antwerpen

Automotive products: 0800 80634

Industrial products: 0800 80635

Fax: 0800 80648

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved