



Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty

Mobil Commercial Vehicle Lube , Caribbean

Mobil commercial-vehicle-lube

Product Description

Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in on and off-highway severe service applications. Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty delivers excellent performance in both modern diesel engines as well as older models. Provides up to an average of 30% more viscosity control¹.

Features	Advantages and Potential Benefits
Provides up to an average of 40% more valve train wear protection ¹	Longer engine life
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life
Thermal and oxidation stability	Controls sludge build-up and deposits

1. Compared to API CH-4 standard. Based on Sequence IIIF and RFWT engine test.

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers.
- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.

Specifications and Approvals

This product has the following approvals:
MB-Approval 228.3
MTU Oil Category 2

This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:

API CH-4

API SJ

Cummins CES 20076

Properties and Specifications

Property	
Grade	SAE 15W-40
Viscosity Index, ASTM D2270	137
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	115.9
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15.21
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Density @ 15 C, kg/l, ASTM D4052	0.87

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2021


ExxonMobil de Colombia S.A.

Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved