

**MOBIL ALTO KILOMETRAJE 25W60**

Mobil Passenger Vehicle Lube , Caribbean

High Mileage Conventional Engine Oil

**Product Description**

Mobil™ Alto Kilometraje is a unique formula that is especially designed for engines with over 100,000 kilometers. The 25W-60 viscosity provides a thick oil film that protect gasoline engines that operate in severe service such as high temperatures and in city traffic where stop-and-go driving is common. Mobil Alto Kilometraje formulated from quality base stocks combined with performance additives, which help protect against the formation of sludge and corrosion.

**Features and Benefits**

Mobil Alto Kilometraje:

- Helps to reduce engine wear and corrosion in higher mileage vehicles
- Protects under a wide variety of operating conditions, especially high temperatures
- Helps reduce oil leakage due to the thick oil film
- Reduce oil consumption

**Applications**

Mobil Alto Kilometraje is recommended by ExxonMobil for higher mileage vehicles including turbo charged, super charged, fuel injected, multi-valve and non aspirated engines. Before using Mobil Alto Kilometraje, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

**Specifications and Approvals**

<b>This product meets or exceeds the requirements of:</b>
API SL
API SJ

**Properties and Specifications**

Property	
Grade	SAE 25W-60
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	24.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	262
Density @ 15 C, g/ml, ASTM D4052	0.899
Pour Point, °C, ASTM D97	-24
Flash Point, Cleveland Open Cup, °C, ASTM D92	270

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil de Colombia S.A.  
Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

