



Mobil™ Hidraulico AW 68 HLP

Mobil Industrial , Brazil

Hydraulic Oil

Product Description

Mobil Hidraulico AW 68 HLP is a good quality anti-wear hydraulic oil intended for industrial and mobile service applications, subjected to moderate operating conditions and requiring anti-wear lubricants.

Mobil Hidraulico AW 68 HLP is formulated to deliver good performance in a range of hydraulic components used in systems subjected to moderate operating conditions.

Features and Benefits

- Good anti-wear performance helps reduce pump wear and prolonging pump life.
- Corrosion protection helps reduce the effects of moisture on system components.
- Filterability to prevent filter blockage even in the presence of water.

Applications

- Systems using gear, vane, radial and axial piston pumps and those containing gears and bearings where mild anti-wear characteristics are required.
- Where hydraulic oil contamination or leakage is unavoidable.
- Where small amounts of water are unavoidable.

Specifications and Approvals

This product meets or exceeds the requirements of:

DIN 51524-2:2017-06

Properties and Specifications

Property	
Grade	ISO 68
Pour Point, °C, ASTM D97	-12
Density @ 15 C, kg/l, ASTM D4052	0.88
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	218
Viscosity Index, ASTM D2270	90

Property	
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	68

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2022

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ – BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved