



## Mobiltac Double Letter Series

Mobil Industrial, Brazil

OPEN GEAR LUBRICANT

### Product Description

The Mobiltac Double Letter Series products are high performance, non-diluent type, heavy-bodied products intended for the lubrication of open gears over a wide of environmental conditions and machine requirements. They incorporate extreme pressure additives for the protection of gear teeth and metal surfaces under extremely heavy loads. They form a cohesive and adhesive lubricating film that resists wear, water wash and excessive "throw off". They lubricate properly boundary conditions. They resist peeling or flaking at sub-zero temperatures. Mobiltac Double Letter Series lubricants are recommended for all-purpose applications in open gears. The two lighter grades meet many builder requirements for heavily loaded splash-type enclosed gearing.

### Features and Benefits

The Mobiltac Double letter Series of products are important members of the Mobiltac brand of products that have been used with great success over several decades in a wide variety of applications. They offer the following features and potential benefits:

- Reduced maintenance costs because of longer gear life resulting from reduced wear and excellent protection against corrosion
- Reduced lubricant consumption due to excellent adhesive qualities and resistance to "throw off" and water wash-out
- Good low temperature properties with resistance to peeling

### Applications:

Mobiltac Double Letter Series lubricants are recommended for all-purpose applications in open gears. The two lighter grades are used in heavily loaded splash-type enclosed gearing. Applications include:

- Machinery components as hoist gears, swing gears, large press gears
- Equipment in forge shops, pit or strip mining
- Large earthmoving equipment and cement kilns

### Properties and Specifications

Property	MOBILTAC LL	MOBILTAC MM	MOBILTAC QQ
Density @ 15 C, kg/l, ASTM D4052	0.916		
Flash Point, Cleveland Open Cup, °C, ASTM D92	182	182	190
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	58	126	208
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	1209	3900	9526

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2024

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01


21930-080 Rio de Janeiro – RJ – BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are permitted.

are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pri may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

The ExxonMobil logo, featuring the word "Exxon" in a bold, sans-serif font and "Mobil" in a similar font, with a stylized "X" connecting the two.A row of four logos: "Exxon", "Mobil", "Esso" (in a circle), and "XTO" (with "EXXON MOBIL" written below it).

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved