



Mobil ATF™ 200

Mobil Passenger Vehicle Lube , Brazil

Automatic Transmission Fluid

Product Description

Mobil ATF 200 is formulated to function as a power transmission fluid in torque converters, a hydraulic fluid in control and servo systems, a lubricant for bearing, gears, a friction controlling medium for the bands and clutches and a heat transfer medium to carry heat generated in transmissions to the gear case or oil cooler.

Due to its high Viscosity Index Mobil ATF 200 undergoes relatively small changes in fluidity regardless of operating or ambient temperatures. This ensures excellent performance as a hydraulic medium giving good operation under high temperature conditions and minimum power losses under cold conditions. control system.

Features and Benefits

Mobil ATF 200 offers the following benefits:

- Correct frictional characteristics give smooth transmission and perfect synchronisation, over a long period under continual severe operating conditions
- Protection against deposit formation and evaporation losses at high operating temperatures with very good low temperature operation
- Good protection against wear, resistance to rust, corrosion and foam
- Compatible with seal materials used in transmission units
- Low maintenance costs, and good operating profits

Specifications and Approvals

This product has the following approvals:
MB-Approval 236.2

This product is recommended for use in applications requiring:
GM Type A Suffix A

Properties and Specifications

Property	
Color, Visual	Vermelho
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	40.1
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	7.5
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	154
Flash Point, Cleveland Open Cup, °C, ASTM D92	188
Density @ 15 C, kg/l, ASTM D4052	0.886

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ – BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved