



Mobil Super Moto™ 4T MX 10W-30 Authentic

Mobil Passenger Vehicle Lube , Brazil

Conventional High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super Moto™ 4T MX 10W-30 Authentic is a high performance semi-synthetic four-stroke motorcycle engine oil primarily intended for general use in many types of four-stroke motorcycles and engines. It's unique formulation provides excellent flow characteristics to reduce engine wear during start-up and outstanding protection of the transmission and the clutch during operation. Its lower viscosity grade (SAE 10W-30) helps the engine to work at a higher level of efficiency, compared to SAE 20W-50.

Features and Benefits

MOBIL SUPER MOTO 4T MX 10W-30 AUTHENTIC provides good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Provides anti-wear protection to help promote long engine and transmission life	
Helps keep your engine cleaner	
Formulated with premium base stocks for increased oxidation stability and less volatility.	
Potential fuel economy compared with oil 20W-50 viscosity which can help reduce emissions.	
Excellent frictional properties for proper performance of the clutch.	

Applications

MOBIL SUPER MOTO 4T MX 10W-30 AUTHENTIC is recommended for 4-stroke motorcycle in which the manufacturer specifies the use of SAE 10W-30. Its formulation provides the adequate level of protection for the engine transmission and clutch, particularly in air-cooled engines, which tend to operate at higher temperatures. It is also especially recommended for 4-stroke engines equipped with catalytic converters to reduce emissions. It is recommended by ExxonMobil for applications requiring API SL oils. Meets or exceeds the latest JASO MA2 performance standard.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MA2
JASO MA2 2016

Properties and Specifications

Property	
----------	--

Property	
Grade	SAE 10W-30
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	70.7
Pour Point, °C, ASTM D97	-45
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	208
Ash, Sulfated, mass%, ASTM D874	0.75

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2021

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO  
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved