



Mobil Super 1000 20W50

Mobil Passenger Vehicle Lube , Brazil

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super™ 1000 product is high quality premium multigrade motor oils designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Mobil Super 1000 20W-50 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Excellent anti-wear protection
- Excellent engine cleanliness

Applications

Mobil Super 1000 20W-50 is suitable for use in gasoline powered vehicles, and is ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions. This product meets or exceeds the requirements of API SL, grade SAE 20W-50.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 20W-50 |
| Viscosity Index, ASTM D2270 | 136 |
| Pour Point, °C, ASTM D97 | -30 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 142.6 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 17.3 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 222 |
| Density @ 15 C, g/ml, ASTM D1298 | 0.8856 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved