



Mobil Ultra 10W-40

Mobil Passenger Vehicle Lube , Belarus

Premium Quality Multigrade Passenger Vehicle Engine Oil

Product Description

Mobil Ultra 10W40 is a premium quality motor oil for many types of gasoline and Diesel vehicles.

Features and Benefits

Mobil Ultra 10W-40 is formulated with a proprietary mixture of premium and super premium quality base oils with an additive technology delivering very high performance and engine protection under a variety of driving conditions. Mobil Ultra 10W-40 reduces engine wear with excellent high and low temperature performance.

Applications

Mobil Ultra 10W-40 can be used in a variety of passenger vehicles , light trucks and vans, and for anyone seeking a dependable super premium quality product.

Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:
MB 229.1

This product meets or exceeds the requirements of the following industry specification:
ACEA A3/B3
API SJ
API SL
API SM
API SN
API SN PLUS

Properties and Specifications

Property	
Grade	SAE 10W-40
Ash, Sulfated, mass%, ASTM D874	1
Density @ 15.6 C, g/ml, ASTM D4052	0.87

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	88.7
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	150

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2022

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved