



Mobil Delvac Extended Life Coolant AntifreezeC Series

Mobil Commercial Vehicle Lube , Canada

EXTENDED LIFE Coolant/Antifreeze – C Series

Product Description

Products:

Mobil Delvac Extended Life Coolant/Antifreeze -C

Mobil Delvac Extended Life 55/45 Prediluted Coolant/Antifreeze -C

Mobil Delvac Extended Life 50/50 Prediluted Coolant/Antifreeze -C

Mobil Delvac Extended Life 60/40 Antifreeze Coolant Pre-diluted

Mobil Delvac Extended Life Coolant/Antifreeze –C Series feature a patented Hybrid and Organic Acid Technology (OAT) formula that protects cooling systems for up to 960,000 km on highway use or 6 years / 12,000 hours of off-highway use when added as an initial fill and properly maintained. Designed for use in on-road, off-road, farm, marine, and stationary applications including but not limited to Caterpillar, Detroit / MTU, GM Heavy Truck, Freightliner, PACCAR and Volvo Mack.

Features And Benefits

- Eliminates the need for SCAs and chemically charged filters, saving time and money.
- Provides long-term elastomer compatibility.

Applications

Mobil Delvac Extended Life Coolant/Antifreeze -C Series are recommended by Imperial Oil for use in cooling systems including Caterpillar, Detroit / MTU, GM Truck, Freightliner, PACCAR and Volvo Mack.

Specifications And Approvals

Mobil Delvac Extended Life Coolant/Antifreeze meets or exceeds the requirements of:

- ASTM D-3306, D-6210
- Japanese Standard JIS K2234
- TMC RP 329B
- Detroit Fluids Specification 7SE298, 93K217
- MTU MTL 5048
- CID-A-A-52624
- Cummins

Typical Properties

Mobil Delvac Extended Life Coolant/Antifreeze -C	
Specific Gravity 20°C / 20°C	1.132
Freezing Point, 50 Vol. %, °C	-37
PH, 50 Vol. %	8.1
Chloride, PPM	20
Reserve Alkalinity, ml	8.2
Water (Wt. %)	4.0
Color	Red

Mobil Delvac Extended Life 55/45 Prediluted Coolant/Antifreeze -C	
Specific Gravity 20°C / 20°C	1.090
Freezing Point, 50 Vol. %, °C	-45 Max.
PH, 50 Vol. %	8.1
Chloride, PPM	25 Max.
Reserve Alkalinity, ml	3.0 Min.
Color	Red

Mobil Delvac Extended Life 50/50 Prediluted Coolant/Antifreeze -C	
Specific Gravity 20°C / 20°C	1.082
Freezing Point, 50 Vol. %, °C	-37 Max.
PH, 50 Vol. %	8.0
Chloride, PPM	25 Max.
Reserve Alkalinity, ml	3.0 Min.
Color	Red

Mobil Delvac Extended Life 60/40 Antifreeze Coolant Pre-diluted	
Specific Gravity 20°C / 20°C	1.09
Freezing Point, 50 Vol. %, °C	-45 Max.
PH, 50 Vol. %	8.5 Max.
Chloride, PPM	25 Max.
Reserve Alkalinity, ml	3.0 Min.
Color	Red

Health And Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil logotype, the Pegasus design, and Mobil Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

11-2019

Imperial Oil

Petroleum and Chemicals Division
Lubricants and Specialties
240 Fourth Ave SW
C. P. 2480, Station M
Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil





© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved