



## Mobil DTE Oil Double Letter Series

Mobil Industrial , Canada

Circulating Oils

### Product Description

The Mobil DTE Oil Double Letter Series of lubricants are high performance heavy duty circulating oils primarily intended for continuous reuse in circulation lubrication systems for gears and bearings. They are formulated from high quality base stocks and a proprietary additive system to provide superior protection against rust, excellent resistance to oxidation and thermal degradation, and a high level of protection against wear, plus excellent resistance to high temperature corrosion of soft metals. They possess good demulsibility that permits water and other contaminants to separate readily from the oil in the system reservoir. The Mobil DTE Oil Double Letter Series are available in two ISO viscosity grades 150 and 220.

The Mobil DTE Double Letter Series family of products provides a versatile lubricant source for a wide range of industrial equipment. They provide the users with very reliable and efficient operation in industrial circulating system applications, as well as other lubricant application methods, including hydraulic systems. They are particularly resistant to the effects of prolonged high temperature exposure and perform very well in circulating systems with short oil residence times. Mobil DTE Double Letter Series oils have very good water separability properties, which allows water to separate readily in the system reservoir. Their high level of anti-wear properties results in exceptional equipment performance that not only results in fewer breakdowns but helps improve production capacity.

This combination of benefits has Mobil DTE Oil Double Letter Series the product of choice for many users around the world, for the last several decades.

### Features and Benefits

The Mobil DTE family of products is well known and highly regarded world-wide based on their outstanding performance and the RandD expertise and the global technical support which stand behind the brand. The highly versatile performance of one series of oils in this family, Mobil DTE Oil Double Letter Series oils, has made them the choice of many users around the world for many decades.

Mobil DTE Named oils enjoy an excellent reputation in the lubrication of the circulation systems of industrial gearboxes, plus a wide variety of ancillary equipment, including hydraulic systems. As designs change and increase in severity, it is the challenge of our scientists to understand the effect of these changes on the lubricant and to formulate these products for the broad versatility they are recognized for.

For the Mobil DTE Oil Double Letter Series of lubricants this process has resulted in the use of a proprietary high quality base stocks for outstanding oxidation stability, plus a unique additive combination to ensure the excellent, wide-ranging performance of these oils. A review of the features, advantages and potential benefits of the product are shown below:

Features	Advantages and Potential Benefits
Excellent thermal/oxidative and chemical degradation resistance	Long lubricant charge life giving extended drain periods and reduced product replacement costs; reduced filter deposits and longer filter life
Outstanding anti-wear performance	Reduced pump wear leading to longer pump life, protection of critical bearings and gearing
Protection against rust and corrosion in both the liquid and vapour phase	Enhanced system cleanliness for reduced maintenance and un-planned stoppages
Good demulsibility and avoids emulsion formation	Improved operating efficiency and lower operating costs
Multiple application capability	Reduced plant inventory savings

### Applications

These oils are intended primarily for the lubrication of plain bearings, roller bearings, parallel shaft and bevel gearing. They are suitable as multipurpose lubricants in systems not subject to shock loading and which do not require extreme pressure performance. They are used in applications using splash, bath and ring oil arrangements and all other application methods involving pumps, valves and auxiliary equipment. They are recommended for use in hydraulic systems where higher viscosity oils are specified.

- Moderate duty spur, bevel, helical and herringbone gear units
- Circulating systems
- Mobil DTE Oil Extra Heavy and BB can also be used in hydraulic systems employing gear, vane, radial and axial piston pumps where anti-wear hydraulic fluids are required and clearances are relatively large
- Certain compressors and vacuum pumps handling air, natural gas and inert gases provided the discharge temperatures do not exceed 150°C

#### Properties and Specifications

Property	MOBIL DTE OIL EXTRA HEAVY	BB
Grade	ISO 150	ISO 220
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1A	1A
Demulsibility, Total Free Water, Non-EP Oils, ml, ASTM D2711	38	36
Density @ 15 C, kg/l, ASTM D1298		0.89
Density @ 15.6 C, lb/USg, ASTM D1298	0.89	
Emulsion, Time to 40/37/3, 82 C, min, ASTM D1401	20	20
FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1	12	12
Flash Point, Cleveland Open Cup, °C, ASTM D92	272	284
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.4	18.8
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	146	218
Pour Point, °C, ASTM D97	-21	-18
Rust Characteristics, Procedure A, ASTM D665	Pass	PASS
Rust Characteristics, Procedure B, ASTM D665	Pass	PASS
Viscosity Index, ASTM D2270	96	96

#### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2023

#### Imperial Oil

Petroleum and Chemicals Division  
Lubricants and Specialties  
240 Fourth Ave SW  
C. P. 2480, Station M  
Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved