



Mobil Pegasus 505 Ultra

Mobil Industrial , Canada

Natural Gas Engine Oil

Product Description

Mobil Pegasus 505 Ultra is a natural gas engine oil that is primarily designed for use in naturally aspirated and turbo-charged 4-cycle natural gas engines. It is spec balanced to perform across mixed fleets of natural gas engines and compressors, excelling where wet gas is present.

Customers have a need to optimize operations and maintenance practices when choosing lubricants for their natural gas engines and compressors. For customer are utilizing "sweetening", or other methods of utilizing the engine oil to feed the compressor, oxidation and nitration stability are not always as important as th lubricant consumption and anti-wear performance. Mobil Pegasus 505 Ultra enables customers in these types of operations to perform their sweetening cost effe while maintaining the anti-scutffing and wear protection needed for long-term equipment life. Customers that are operating with wet gas applications often must multiple lubricants for the natural gas engines and compressors, as downstream emulsion formations can be caused when utilizing other natural gas engine oils compressors. When customers have a need to utilize one lubricant for both applications, Mobil Pegasus 505 Ultra has an advanced additive package that e consolidation, resulting in reduced expenses and improved operational productivity.

For customers who do not utilize sweetening or do not operate in areas with wet gas, Mobil Pegasus 505 Ultra is designed to help customers reduce their ope expenses through lower oil consumption. The lower oil consumption comes as a result of lower daily lubricant consumption, and a reduced number of oil changes.

Features and Benefits

Mobil Pegasus 505 Ultra is designed to help customers run their operations efficiently and cost effectively, especially in wet gas and sweetening applications:

Features	Advantages and Potential Benefits
Well-balanced advanced technology additive system for mixed fleet and wet gas applications	Enables customers to consolidate to one lubricant, thereby reducing lubricant tank requirements expenses across their fleet
Lower volatility and oil consumption	Lower daily oil consumption (by up to 50% versus Mobil Pegasus 505 depending on operating cond and equipment), helping customers reduce annual oil spend
Good oxidation and nitration resistance	Longer oil life (up to twice the oil drain interval of Mobil Pegasus 505 depending on operating cond and equipment), leading to lower inventory costs and reduced maintenance spend
Effective corrosion protection, water separation, and overall deposit control	Protects against harmful contaminants like water while optimizing overall engine cleanliness, ene customers to extend overhaul capabilities and reduce operating expenses
Good anti-wear and anti-scutff protection	High level of protection in engines, enabling customers to extend top end and overhaul capabilities reduce operating expenses

Applications

- Heavily loaded 4-cycle natural gas engines requiring anti-scutff protection
- Reciprocating compressor compressing natural gas, including wet gas
- Naturally aspirated or turbocharged natural gas engines
- Recommended for natural gas engines requiring 0.5% sulfated ash

- Appropriate for use in natural gas engines: Caterpillar, Waukesha, Cummins, Arrow and other small horsepower field units, and many more
- Appropriate for use in compressors: Ariel, Dresser-Rand, and other other reciprocating compressors

Properties and Specifications

Property	
Grade	SAE 40
Density 15 C, kg/L, CALCULATED	0.886
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.1
Total Base Number, mgKOH/g, ASTM D2896	2.7
Ash, Sulfated, mass%, ASTM D874	0.46
Flash Point, Cleveland Open Cup, °C, ASTM D92	274
Viscosity Index, ASTM D2270	97
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	126
Pour Point, °C, ASTM D97	-30

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Imperial Oil

Petroleum and Chemicals Division
Lubricants and Specialties
240 Fourth Ave SW
C. P. 2480, Station M
Calgary AB T2P 3 M 9
1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All produc not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved