



Mobil Super 3000 Formula D1 0W-20

Mobil Passenger Vehicle Lube , Canada

Product Description

Mobil Super™ 3000 Formula D1 0W20 is a synthetic motor oil, which provides excellent high temperature protection even under severe operating conditions. Mobil Super 3000 is designed to help provide long engine life and outstanding protection in vehicles of all ages. Mobil Super 3000 provides outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super 3000 Formula D1 0W20, is classified by The American Petroleum Institute (API) as a "Resource Conserving" engine lubricant and meets or exceeds ILSAC GF-5 and API service SN. Those claims are backward compatible with earlier performance levels such as API SM, SL, and SJ and previous ILSAC categories.

Mobil Super 3000 Formula D1 0W20 is approved against GM dexos1™ Gen 2 under the license D10164GJ015.

Features and Potential Benefits

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high temperature protection to help keep engines cool
- Permits extended operation at elevated temperatures (up to 400° F) without oxidative oil thickening and oil breakdown
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Meets or exceeds the latest industry specifications
- API SN Resource Conserving

Applications

- Mobil Super 3000 Formula D1 0W20 is recommended for gasoline fueled automobiles where a 0W-20 viscosity is required. It meets or exceeds the requirements of API SN, SM and ILSAC GF-5 (Starburst Certification Symbol)

Specifications and Approvals

Mobil Super 3000 Formula D1 0w-20 meets or exceeds the requirements of:	
API SN	X
API SM	X
ILSAC GF-5	X

Mobil Super 3000 Formula D1 0w-20 has the following builder approvals:	
GM dexos1™ Gen 2 under license D10164GJ015	X

Typical Properties

Mobil Super 3000 Formula D1	0w-20
API Service Classification	SN
Gravity, API	35.4

Mobil Super 3000 Formula D1	0w-20
Specific Gravity	0.848
Pour Point, °C (°F)	-42(-44)
Flash Point, °C (°F), ASTM D 92	238(460)
Viscosity	
cSt at 40°C	44.9
cSt at 100°C	8.6
CCS, cP	5670@-35°C
MRV, cP	
Viscosity Index	
Resource Conserving	

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil, Mobil 1 and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

04-2021

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved