



**Mobilgrease™ MB 2**  
Mobil Grease , Switzerland  
Automotive Grease

**Product Description**

Mobilgrease MB 2 is a lithium thickened grease for multi purpose applications in commercial and passenger vehicle cars. It is based on mineral oil with a viscosity c 180 cSt. The product has excellent oxidation stability and very good water resistance. It also offers excellent corrosion protection and good flow properties even temperatures.

Mobilgrease MB 2 conforms to Mercedes Benz page 267.

Mobilgrease MB 2 is compatible with seals made of NBR, ACM and FKM, as long as these are suitable for the operating temperatures.

**Features and Benefits**

Features	Advantages and Potential Benefits
Can be used in a wide variety of automotive applications	Potential to rationalise products
Long service life	Reduced operating costs from lower maintenance costs and economic usage
Good oxidation and thermal stability	Good equipment reliability and availability
Excellent protection against rust and corrosion and resistance to water washout	Enhanced equipment protection and good lubrication even in presence of wa
Good pumpability in centralised systems at low temperatures	Optimum reliability
Good mechanical stability even at high shear rate	Longer service intervals

**Applications**

Mobilgrease MB 2 can be used for many automotive applications. It can be used as a single multi purpose grease in fleets, agricultural and construction equipment MB page 267 specification has been recommended. Mobilgrease MB 2 can also be used in some industrial applications where a non EP grease is suitable. The p has a speed bearing factor of approximately 200,000DmN.

**Specifications and Approvals**

<b>This product has the following builder approvals:</b>
MAN 283 Li-P 2
MB-Approval 267.0
<b>This product meets or exceeds the requirements of:</b>
DIN 51825:2004-06 - KP 2 K -30

**Properties and Specifications**

Property	
Grade	NLGI 2
Thickener Type	Lithium
Base Oil Viscosity of Greases @ 40 C, mm2/s, AMS 1697	180
Color, Visual	BROWN
Dropping Point, °C, ASTM D2265	>190
Four-Ball Wear Test, Weld Load, N, DIN 51350-4	2600
Oil Separation, 168 h @ 40 C, mass%, DIN 51817	6.5
Flow Pressure @ -30C, mbar, DIN 51805	<1400

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023  
EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)  
POLDERDIJKWEG  
B-2030 Antwerpen  
Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved