



## Mobil Super 3000 0W-20

Mobil Passenger Vehicle Lube , Cote divoire

Synthetic Motor Oil

### Product Description

Mobil Super™ 3000 is a synthetic engine oil, which provides excellent high temperature protection even under severe operating conditions. Mobil Super 3000 is designed to help provide long engine life and outstanding protection in vehicles of all ages. Mobil Super 3000 provides outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super 3000 0W-20, is classified by the American Petroleum Institute (API) as a "Resource Conserving" engine lubricant and meets or exceeds ILSAC GF-6A and API SP. Those claims are backward compatible with earlier performance levels such as API SN, SM, SL, and SJ and previous ILSAC categories.

### Features and Benefits

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high temperature protection to help keep engines cool
- Permits extended operation at elevated temperatures (up to 200°C) without oxidative oil thickening and oil breakdown
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Meets or exceeds the latest industry specifications (API SP Resource Conserving; ILSAC GF-6A)

### Applications

Mobil Super 3000 0W-20 is recommended for gasoline fueled automobiles where a 0W-20 viscosity is required. It meets or exceeds the requirements of the latest API and ILSAC industry specs for modern fuel efficient engines. It also meets Ford's latest specifications for 0W-20 engine oils and is suitable for use in Honda, Toyota, Kia... hybrid vehicles where a 0W-20 / API SP (or lower) engine oil is required.

### Specifications and Approvals

This product meets or exceeds the requirements of:
API SJ
API SL
API SM
API SN
API SN Resource Conserving
Ford WSS-M2C947-A
API SN PLUS

**This product meets or exceeds the requirements of:**

API SN PLUS RESOURCE CONSERVING

API SP

API SP Resource Conserving

ILSAC GF-6A

Ford WSS-M2C947-B1

FORD WSS-M2C962-A1

**Properties and Specifications**

Property	
Grade	SAE 0W-20
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Flash Point, Cleveland Open Cup, °C, ASTM D92	220
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	44.9
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	170

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

MOBIL OIL COTE D'IVOIRE

Route de Petit Bassam 15, BP 900

Abidjan 15

+ 225 21 75 37 00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved