



MOBIL FLEET 15W-40

Mobil Commercial Vehicle Lube , Chile

Diesel Engine Oil

Product Description

MOBIL FLEET 15W-40 is an oil designed to meet warranty requirements for high-speed, four-stroke heavy duty diesel engines. This product is formulated to maintain durability of emission control systems, including diesel particulate filters and other advanced aftertreatment systems.

Fully backward compatible, MOBIL FLEET 15W-40 is suitable for both newer and older heavy duty engine designs. Accordingly, this oil meets or exceeds requirements of API CJ-4, CI-4 PLUS, CI-4 service categories. Also approved by major original equipment manufacturers (OEM). MOBIL FLEET 15W-40 may also be used in gasoline engines requiring the API SM specification.

Applications

Recommended for use in high performance diesel applications including low emission engines designs, including those featuring EGR technology.

Recommended for use in high performance gasoline engines and mixed fleet operators.

Specifications and Approvals

This product has the following approvals:
Mack EO-O Premium Plus
MTU Oil Category 2.1
VOLVO VDS-4

This product meets or exceeds the requirements of:
API CH-4
API CI-4
API CI-4 PLUS
API CJ-4
API SM
Caterpillar ECF-2
Caterpillar ECF-3
Cummins CES 20081

Properties and Specifications

Property	
Grade	SAE 15W-40

Property	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	112
Specific Gravity, 15.6 C/15.6 C, ASTM D4052	0.88
Total Base Number, mgKOH/g, ASTM D2896	10
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Pour Point, °C, ASTM D5950	-33
Viscosity Index, ASTM D2270	134
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023  
COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XT

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved