



Mobil Delvac Super Multigrades

Mobil Commercial Vehicle Lube , Chile

Heavy Duty Engine Oils

Product Description

Mobil Delvac Super 10W-30, 15W-40 and 20W-50 are high performance, heavy duty engine oils that provide proven protection to diesel engines operating in sev and off-highway service applications. Mobil Delvac Super Multigrade engine oils are recommended for use in a wide range of heavy duty applications and ope environments found in the trucking, construction, and agricultural industries. They are also suitable for gasoline engines.

Features and Benefits

The key benefits of Mobil Delvac Super Multigrades include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On highway light and heavy duty trucking
- Off highway industries including: trucking, construction, quarrying, and agriculture
- Mixed diesel/gasoline engine fleets

Specifications and Approvals

This product is recommended for use in applications requiring:	10W-30	15W-40	20W-50
API CF-4	X	X	X
API SF	X	X	X
API SG		X	X

Properties and Specifications

Property	10W-30	15W-40	20W-50
Grade	SAE 10W-30	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	0.8	0.8	0.8
Density @ 15.6 C, g/ml, ASTM D1298			0.88

Property	10W-30	15W-40	20W-50
Density @ 15.6 C, g/cm3, ASTM D4052	0.88	0.88	
Flash Point, Cleveland Open Cup, °C, ASTM D92	224	234	244
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.5	14.3	17.6
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	76	105	149
Pour Point, °C, ASTM D97	-33	-27	-30
Total Base Number, mgKOH/g, ASTM D2896	8.2	8.2	8.2
Viscosity Index, ASTM D2270	146	139	129

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
COPEC S.A.
Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved