



Mobil Super™ 2000 Formula P 10W-40

Mobil Passenger Vehicle Lube , Chile

Passenger Vehicle Motor Oil

Product Description

The Mobil Super™ 2000 range of lubricants are enhanced-premium semi-synthetic engine oils, designed to provide an excellent level of protection and performance.

Features and Benefits

Mobil Super™ 2000 products are industry tested so you can trust you will get the performance you want from your vehicle.

Mobil Super™ 2000 Formula P 10W-40 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent cold temperature protection

Applications

Mobil Super™ 2000 products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend Mobil Super™ 2000 if you occasionally experience demanding driving conditions:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions
- High Performance Engines

Specifications and Approvals

This product has the following approvals:
PSA B71 2300

This product is recommended for use in applications requiring:
MB 229.1
API CF

This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

API SN PLUS

ACEA A3/B3

ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 10W-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Ash, Sulfated, mass%, ASTM D874	1.2
Phosphorus, mass%, ASTM D4951	0.1
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	97
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.4
Density @ 15.6 C, g/ml, ASTM D4052	0.87

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

Compañía de Petróleos de Chile Copec SA

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExonMobil

Exxon

Mobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved