



Mobil Delvac Modern 15W-40/20W-50 Super Defense V2

Mobil Commercial Vehicle Lube , 中国

Synthetic Technology

Product Description

Mobil Delvac Modern 15W-40/20W-50 Super Defense V2 is a high performance synthetic technology diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. It is recommended by ExxonMobil for use in a wide range of heavy duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

Mobil Delvac Modern 15W-40/20W-50 Super Defense V2 is formulated using high performance base oils and a balanced additive system to provide optimum engine performance in modern diesel engines. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Cleaner engines and longer component life
Improved soot handling	Improved viscosity control and used oil pumpability
Component compatibility	Longer gasket and seal life

Applications

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product meets or exceeds the requirements of:	15W40	MOBIL DELVAC MODERN 20W-50 SUPER DEFENSE V2
API CI-4	X	X
API SL	X	

Properties and Specifications

Property	15W40	MOBIL DELVAC MODERN 20W-50 SUPER DEFENSE V2
----------	-------	---

Property	15W40	MOBIL DELVAC MODERN 20W-50 SUPER DEFENSE V2
Grade	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	1.1	1.1
Density @ 15 C, kg/m3, ASTM D4052	0.869	0.88
Flash Point, Cleveland Open Cup, °C, ASTM D92	225	227
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.6	19.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	110	169
Pour Point, °C, ASTM D97	-33	-30
Total Base Number, mgKOH/g, ASTM D2896	9	9
Viscosity Index, ASTM D2270	136	130

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved