



## Mobil Delvac™ HDEO 15W-40 V1

Mobil Commercial Vehicle Lube , 中国

Synthetic Technology

### Product Description

Mobil Delvac™ HDEO 15W-40 V1 CK-4 is designed to address needs of engines after the China IV non-road tailpipe emission standards was launched, as well as to provide effective protection for the engine.

### Features and Benefits

- Synthetic Technology
- Designed for China IV1 non-road emission standards and DPF protection<sup>2</sup>
- Long ODI
- Fuel Economy

<sup>1</sup>For specific lubrication requestion and ODI, please refer to OEM's service guide book.

<sup>2</sup>Applied to Mobil Delvac Construction Engine Oil CK-4

### Applications

Recommended by ExxonMobil for use in:

- Heavy duty diesel engines including low emission equipment designed for China off-highway

### Specifications and Approvals

#### This product has the following approvals:

Cummins CES 20081

Cummins CES 20086

#### This product meets or exceeds the requirements of:

API CK-4

### Properties and Specifications

Property	
Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-27
Flash Point, Cleveland Open Cup, °C, ASTM D92	225

Property	
Ash, Sulfated, mass%, ASTM D874	1.0
Total Base Number, mgKOH/g, ASTM D2896	10
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	112
Specific Gravity, 15.6 C/15.6 C, ASTM D4052	0.875
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.2

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved