



## MOBIL DELVAC MODERN 10W40 ADVANCED PROTECTION

Mobil Commercial Vehicle Lube , 中国

Emission System Protection Diesel Engine Oil

### Product Description

Mobil Delvac Modern™ 10W-40 Advanced Protection is a synthetic extra high performance diesel engine oil engineered to provide lubrication to modern, high performance, low emissions engines used in severe applications. This engine oil is designed using high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control. The new advanced additive system has been expertly engineered to help towards long engine life(1) and maintain the efficiency of emission reduction systems including the Diesel Particulate Filter (DPF). Its specifications and approvals allow Mobil Delvac Modern 10W-40 Advanced Protection to target mixed fleet applications.

### Features and Benefits

High output, low emission engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers, and turbochargers increase thermal stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure, retarded timing and aftertreatment devices all require improved oil performance in areas such as oxidation stability, soot dispersancy, volatility and compatibility with aftertreatment devices. The advanced technology in Mobil Delvac Modern 10W-40 Advanced Protection delivers exceptional performance, long drain interval capability and protection of exhaust systems including those fitted with Diesel Particulate Filters (DPF). The key benefits include:

Features	Advantages and Potential Benefits
Outstanding protection against oil thickening, high temperature deposits, sludge build-up and, oil degradation	Provides capability for long drain intervals Helps to protect against ring sticking
Excellent anti-wear, anti-scuff properties and bore polishing and corrosion protection	Helps towards long engine life(1)
Stay-in-grade shear stability. Very low volatility	Helps to reduce viscosity breakdown and oil consumption under heavy duty, high temperature operating conditions
Low ash, sulfur and phosphorous levels	Helps to protect exhaust systems devices like those fitted with DPF
Excellent low temperature properties	Helps to improve pumpability and oil circulation
	Disclaimer (1) Well formulated oils, like Mobil Delvac, that meet or exceed industry or OEM specifications, can help protect engines. Consult OEM for optimum fluid selection. Actual results may vary depending on OEM requirements, type of engine and its maintenance, application and service conditions, and prior lubricant used.

### Applications

- Heavy Duty Diesel Engines including Euro V/VI Modern Low Emissions Vehicles, Utilizing Technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR)
- Heavy Duty Diesel Engines using low sulfur diesel fuels and many biodiesel fuel formulations
- Naturally Aspirated and Turbo-Charged Diesel Powered Equipment
- On-Highway Short-Haul and Long-Haul Trucks and Buses
- Off-Highway Mining, Construction and Agricultural Equipment

(2) Please refer to the owners handbook for OEM application requirements and oil drain intervals for your vehicle or equipment

## Specifications and Approvals

**This product has the following approvals:**

MACK EOS-4.5

MACK EO-O Premium Plus

RENAULT TRUCKS RLD-3

RENAULT TRUCKS RLD-2

VOLVO VDS-4.5

VOLVO VDS-4

VOLVO VDS-3

MTU Oil Category 3.1

MAN M 3775

MB-Approval 228.51

DQC IV-18 LA

MB-Approval 228.31

ZF TE-ML 04C

ZF TE-ML 23A

**This product is recommended for use in applications requiring:**

MAN M 3575

**This product meets or exceeds the requirements of:**

ACEA E9

ACEA E7

ACEA E6

ACEA E4

API CK-4

API CJ-4

API CI-4 PLUS

API CI-4

**This product meets or exceeds the requirements of:**

API CH-4

JASO DH-2

Caterpillar ECF-3

CUMMINS CES 20086

CUMMINS CES 20081

DAF Extended Drain

**Properties and Specifications**

Property	
Grade	SAE 10W-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	153
Density @ 15.6 C, kg/l, ASTM D4052	0.861
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	91
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.7

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

ExxonMobil (China) Investment Co. Ltd  
17th Floor, Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 2000030  
China

+86 21 24076000


<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExonMobil**



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved