



Mobil Vactra™ Ultra 68

Mobil Industrial , 中国

Way and Slide Lubricants

Product Description

Mobil Vactra™ Ultra 68 is a high precision slideway lubricant specifically designed for linear motion guides, ball screws and slideways of machine tools and metal processing machines. In particular, Mobil Vactra Ultra 68 demonstrates exceptional friction performance and coolant separability.

Features and Benefits

Mobil Vactra™ Ultra 68 has been specifically designed to provide machinery protection and machining accuracy by satisfying the stringent demands of machine tool slideways. Mobil Vactra™ Ultra 68 exhibits excellent lubricity and load-carrying performance contributing significantly to improving the quality of machined parts even at sub-micron level.

Mobil Vactra™ Ultra 68 has been developed with significantly enhanced adhesiveness which prevents lubricants from being washed away from slideways. Lubricant wash-away by coolant can be responsible for abnormal noises, increase in sliding resistance, overload of sliding motors stopping operations and decrease in machining accuracy. Mobil Vactra™ Ultra 68 can help prevent these disturbances, even when high-level washing performance coolants are used.

Mobil Vactra™ Ultra 68 can help minimize formation of adhesive deposits on machine tool slideways due to its excellent compatibility with coolants.

In addition, Mobil Vactra™ Ultra 68 demonstrates outstanding separability from coolants which allows the machine tool to operate with optimal precision and helps maximize the life and performance of coolants.

Features	Advantages and Potential Benefits
Controlled frictional characteristics	Reduce stick slip and improve machining accuracy even at sub-micron level
Adhesiveness	Prevent washing lubricant out of the critical surfaces
Water and Aqueous Coolant Separability	Helps improve the life and performance of many aqueous coolants
Long term rust and corrosion protection	Helps reduce the deterioration of sliding surfaces in the presence of water and aqueous coolants

Applications

Mobil Vactra™ Ultra 68 is suitable for the following applications:

- Machine tools using aqueous coolants
- Lubrication of ball screws, linear motion guides (linear motion rolling bearings), head stocks and feeding screws
- Machine tools with shorter coolant replacement intervals due to mixing of slideway lubricants in the coolants
- Machine tools with the formation of adhesive substances on sliding surface and resultant negative effects in lubrication

Specifications and Approvals

This product has the following approvals:

This product has the following approvals:

Takamatsu Machinery

This product meets or exceeds the requirements of:

China GB 11118.1-2011, L-HG

DIN 51502:1990-08 CGLP

Properties and Specifications

Property	
Grade	ISO 68
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	69.9
Pour Point, °C, ASTM D97	-32
Copper Strip Corrosion, ASTM D130	1B
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.4

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExonMobil

Exxon

Mobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved