



Mobil Super™ 2000 Synthetic 5W-30

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

Mobil Super™ 2000 Synthetic 5W-30 is full synthetic engine oils, designed to provide fast protection for engines against tough conditions in city driving.

Features and Benefits

Mobil Super 2000 Synthetic 5W-30 provides:

- Outstanding anti-wear protection for vehicles of all ages against tough conditions in city driving.
- Outstanding protection against harmful deposits to maintain engine cleanliness.
- Outstanding protection against LSPI (low speed pre-ignition) events in TGDl engines to help prolong engine life.
- Low temperature fluidity for smooth start-up, plus exceptional viscosity stability at high operating temperatures

Applications

Mobil Super 2000 Synthetic 5W-30 is formulated to give you confidence of engine protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Passenger cars, SUV's, and high performance vehicles
- Engines with Turbo-Chargers
- Highway cruising
- Normal to occasionally severe operating conditions
- Stop and Go City Driving

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
FORD WSS-M2C929-A
GM 6094M
This product meets or exceeds the requirements of:
API SJ
API SL
API SM

This product meets or exceeds the requirements of:

API SN

API SN PLUS

Ford WSS-M2C946-A

API SN RESOURCE CONSERVING

FORD WSS-M2C946-A

FORD WSS-M2C946-B1

API SP

ILSAC GF-6A

FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	64
Viscosity Index, ASTM D2270	158
Density @ 15.6 C, g/ml, ASTM D4052	0.857
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	228
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	8.5
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	13800
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.1

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2021

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved