



Mobil Super™ Tailored Protection 0W-20

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

Mobil Super™ Tailored Protection 0W-20 is a full synthetic engine oil, designed to keep you worry free from complex road condition with instant protection of e
Mobil Super™ Tailored Protection 0W-20 helps to improve fuel economy while the same time provide fast and stable wear protection to engines.

Features and Benefits

- Formulated to help to enhance fuel efficiency while at the same time provide engine strong wear protection with unique Heat Activated technology
- Patented SpectraSyn Elite™ technology enable the strength and stability of oil film to provide lasting protection to engine
- Extend engine life with protection to LSPI problem of turbo engine
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Meets or exceeds the latest industry specifications

Applications

Mobil Super™ Tailored Protection 0W-20 is recommended for gasoline fuel-efficient vehicles with 0W-20 visosity grade recommended.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SP
ILSAC GF-6A
FORD WSS-M2C962-A1
API SN
API SN PLUS

Properties and Specifications

Property	
Grade	SAE 0W-20
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	14000
Ash, Sulfated, mass%, ASTM D874	0.8
Density @ 15 C, g/ml, ASTM D1298	0.845
Flash Point, Cleveland Open Cup, °C, ASTM D92	237
Viscosity Index, ASTM D2270	161
Total Base Number, mgKOH/g, ASTM D2896	8.8

Property	
Pour Point, °C, ASTM D97	-48
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	46
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.4
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2022
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved