



Mobil 1™ 5W-30

Mobil Passenger Vehicle Lube , 中国

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ 5W-30 is an advanced full synthetic engine oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. Mobil 1™ 5W-30 meets or exceeds the requirements of the industry's toughest standards. Mobil 1 technology comes as standard equipment in many different vehicles, including select high-performance vehicles.

Features and Benefits

- Helps prevent deposits and sludge build-up to enable long engine life
- Excellent overall lubrication and wear protection performance for many driving styles
- Aids fuel economy
- Quick cold weather starting for ultra fast protection
- Provide LSPI protection

Applications

Mobil 1™ 5W-30 is a general purpose engine oil for many types of cars.

Specifications and Approvals

This product has the following approvals:
GM Dexos1 Gen3
HONDA/ACURA HTO-06

This product is recommended for use in applications requiring:
FORD WSS-M2C946-A
Ford WSS-M2C946-B1
Ford WSS-M2C929-A
GM 6094M
GM 4718M
FIAT 9.55535-CR1

This product meets or exceeds the requirements of:
API SJ

This product meets or exceeds the requirements of:

API SL

API SM

API SN

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SP

API SP Resource Conserving

ILSAC GF-6A

ACEA A5/B5

ACEA C2

CHRYSLER MS-13340

FORD WSS-M2C961-A1

Chrysler MS-6395

Properties and Specifications

Property	
Grade	SAE 5W-30
Pour Point, °C, ASTM D97	-39
Ash, Sulfated, mass%, ASTM D874	0.76
Total Base Number, mgKOH/g, ASTM D2896	9.2
Density @ 15.6 C, g/ml, ASTM D4052	0.852
Viscosity Index, ASTM D2270	157
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	13700
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	61
Flash Point, Cleveland Open Cup, °C, ASTM D92	235

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2022

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil**Exxon****Mobil**

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved