



Mobil Super 2000 Synthetic

Mobil Passenger Vehicle Lube , 中国

Fully Synthetic Passenger Vehicle Engine Oil

Product Description

The Mobil Super 2000 Synthetic 5W-30 and 5W-40 are fully synthetic engine oils, designed to provide an excellent level of protection and performance.

Features and Benefits

Mobil Super 2000 Synthetic 5W-30 and 5W-40 contain ExxonMobil patented SpectraSyn Elite™ and Anti-wear component which increases engine efficiency.

Mobil Super 2000 Synthetic provides:

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Maintains engine cleanliness
- Permits extended operation at high temperature

Applications

Mobil Super 2000 Synthetic products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines
- Stop and Go City Driving Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 2000 Synthetic meets or exceeds the requirements of:	5W-30	5W-40
API SN	X	X
API SM	X	X

Mobil Super 2000 Synthetic is also recommended by ExxonMobil for use in applications requiring:	5W-30	5W-40
API CF	X	X

Typical Properties

Mobil Super 2000 Synthetic		
SAE Grade	5W-30	5W-40

Mobil Super 2000Synthetic		
Viscosity, ASTM D 445		
cSt @ 40° C	58	85
cSt @ 100° C	10.1	14.1
Viscosity Index, ASTM D 2270	162	170
Sulfated Ash, wt%, ASTM D 874	0.9	0.9
HTHS Viscosity,, mPa•s @ 150° C, ASTM D4683	3.0	3.5
Pour Point, °C, ASTM D 97	-32	-36
Flash Point, °C, ASTM D 92	222	228
Density @15° C kg/l, ASTM D 4052	0.86	0.86

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommend provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used produc care to protect the environment

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

12-2020
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTON

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved